



EUROCOWL

Flue & Chimney Solutions

Tel: 023 806 3179

Email: info@eurocowl.co.uk

2026



Mini EuroCowl & EuroMAX

Multi Fuel - Gas - Oil - ANTI-DOWNDRAUGHT COWL

Prevents downdraught caused by adverse wind conditions whatever the wind direction.

One piece construction with no moving parts, requiring no maintenance.

Also prevents birds, vermin and water ingress. Supplied fully assembled.

The Stainless Steel 316g can be supplied with or without pre-fitted stainless bird guard mesh.

All versions are available powder-coated in: Terracotta, Cotswold Stone, Black, Sienna and Natural.

High Dome allows effective sweeping.

Universal - fits chimney pots from 125mm to 250mm. Alternative bases enables its use with flexible liners or rigid system chimneys (Twin Wall flues).

Tested by BSRIA to BS715-1993 & BSEN1856—2003. Stainless steel model CE Approved.

Fixings included: band/strap.



Product Code

93-EUR/MCSS + Colour

93-EUR/EMAX + Colour



Mini Hanging EuroCowl

Multi Fuel - Gas - Oil - ANTI-DOWNDRAUGHT COWL

Prevents downdraught caused by adverse wind conditions whatever the wind direction.

One piece construction so no moving parts or maintenance.

Also prevents birds, vermin and water ingress.

Supplied fully assembled.

The Stainless Steel 316g can be supplied with or without pre-fitted stainless bird guard mesh.

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural.

High Dome allows effective sweeping.

Supplied for either 5" (125mm) or 6" (150mm) Flexible flue liners. Alternative variants enables its use with chimney pots or rigid system chimneys (Twin Wall) flues.

Tested by BSRIA to BS715-1993 & BSEN1856—2003.

Stainless Steel model CE Approved.

Fixings included are band/strap.

Covered by our Money Back Guarantee.



Product Code

93-EUR/MHCOWL5 + Colour

93-EUR/MHCOWL6 + Colour



Pot Hanging Cowl

The Euro Pot Hanger features a one-piece construction with no moving parts to install.

Supplied in 316g stainless steel for corrosion resistance and longer life of the cowl.

With its single-piece construction, the Euro Pot Hanger simply fits on the pot and is secured with a Jubilee band(s) saving time on site.

The Euro Pot Hanger design includes sprung clamps for the liner, supporting legs and an additional Jubilee band for secure fixing if required.

5" and 6" Diameter Mesh to match the flue liner allowing for easy and efficient sweeping on all areas of the cowl.

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural.

Product Code

93-EUR/PHCOWL5 + Colour

93-EUR/PHCOWL6 + Colour





Euro Topguard & Topguard 2

Prevents birds, vermin and leaves from entering the flue whilst maintaining flue efficiency. Provides good ventilation and added protection from wind and rain.

Stainless Steel or Mild Steel, fully welded and Zinc plated

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural*

Topguard (with base flange and standard fixing kit) or
Topguard 2 (without base flange and 3 welded straps)
both available in Standard Height or Low Profile varieties.

Suitable for all fuels and appliances including DFE and
LFE gas fires. We strongly recommend the use of
Stainless Steel for solid fuels, smokeless fuels and/or in
coastal areas.

High Dome design allows for effective sweeping.

Universal fit for 125mm to 250mm chimney pots.

Complies with BS5871—Terminals up to 250mm.

Top Guards fixings: nuts and bolts with band/strap method.

Top Guard 2 is fitted with a strap fixing method.



Product Code

93-EUR/TG (SS or MS) (LP) + Colour

93-EUR/TG2 (SS or MS) (LP) + Colour



Flue Liner Adaptors

Designed to support flexible flue liners and enable Mini Eurocowl (anti-downdraught) Cowl or Standard Euro Topguard to be fitted as required.

Material: 316 grade
Stainless Steel

Available in 5" (125mm)
or 6" (150mm)

Product Code

93-EUR/PH5+ Colour

93-EUR/PH6+ Colour

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural

Twin Wall Adaptors

Designed to seal the top of open or damaged rigid system chimneys (Twin Wall) flues and enable Mini Eurocowl (anti-downdraught) Cowl or Standard Euro Topguard to be fitted as required.



Material: 316 grade Stainless Steel

Available in; 5" (125mm) or
6" (150mm)

Product Code

93-EUR/TWA5+ Colour

93-EUR/TWA6+ Colour

All versions are available powder coated in;
Terracotta, Cotswold Stone, Black, Sienna and Natural

Euro TopCap - Closure Cowl

Top Cap for used (when raised) and disused flues.
Protects the Flue from rain ingress whilst providing ventilation, acts as an effective rain cap for active flues.
To match existing terminals and Product Range.

Finish: Made in Stainless Steel or Aluminium.

Fits: Chimney pots: 5"(125mm) to 10"(250mm) diameter.

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural*



Product Code

93-EUR/TC (SS or A) + Colour

Flue Liner Clamps

Chimney cowl clamp & Sleeve Kits are designed for use with all manufacturers sized flexible liners this is due to their unique clamshell design and adjustment fixings.

In conjunction and to enable either;
Mini Eurocowl (anti-downdraught) Cowl or
Standard Euro Topguard to be fitted as required.

The Clamp allows for backfilling with its clamshell design.

The Sleeve works as a flexible liner hanger,
available in 5" (125mm) or 6" (150mm).

The Clamp & Sleeve can be
purchased as a kit or individually.

Product Code

93-EUR/FLK5+ Colour

93-EUR/FLK6+ Colour



Fits: Chimney pots: 5" (125mm) to 10" (250mm) diameter.
Enables cowl to be removed for maintenance / inspection

Large Diameter Birdguards (Available Bespoke Sized)

Prevents birds, vermin and leaves from entering the flue whilst maintaining flue efficiency. Provides good ventilation and added protection from wind and rain.

Standard sizes: 287mm /
300mm / 318mm / 350mm
/ 400mm / 500mm



Product Code

93-EUR/TGL (SS or MS) (*) + Colour**

Stainless Steel* or Mild Steel fully welded.

*(Stainless Only available on up to 350mm)

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural*

Supplied with colour matching extra long length straps with nuts and bolts and a Jubilee band to secure the

Square Birdguards

(Available Bespoke Sized)

Prevents birds, vermin and leaves from entering the flue whilst maintaining flue efficiency. Provides good ventilation and added protection from wind and rain.

Standard Sized; 200mm & 300mm



Product Code

**93-EUR/SQTG (SS or MS)
+ (***) + Colour**

Available in Stainless Steel.
or Mild Steel fully welded.

All versions are available powder-coated in:
Terracotta, Cotswold Stone, Black, Sienna and Natural*

Supplied with colour matching long length straps to and jubilee band and nuts and bolts to secure the cowl.



We can supply additional or alternative fixing kits.

- Standard Band and Strap (Incl Jubilee Band(s))
- Hook Bolts Kit (Where Jubilee isn't suitable)
- Anchor Bolts (Where potentially no Pot is Present)

Our Standard Powder-Coated Finishes available:
Terracotta, Cotswold Stone, Black, Sienna and Natural*



*Natural finish is only available on Stainless Steel products
On Order please use codes below and end with colour:

N = Natural*
T = Terracotta
S = Sienna
B = Black
C = Cotswold Stone

**We offer a bespoke service if a project requires additional requirements, colour finishes or applications.
Please enquire.**



10 Year Guarantee



All stainless steel Eurocowl products are covered by a 10 year guarantee against faulty materials and/or workmanship.

Mild Steel products remain covered by our 12 month guarantee.

Both guarantees require the burning of appropriate fuels and that the chimneys have been regularly serviced, swept and maintained and used appropriately.

In addition anti-downdraught cowls of our manufacture carry a further guarantee as follows:-

If the cowl fails to cure a downdraught problem after a reasonable testing time of three months it can be returned to the supplier together with proof of purchase for a full refund provided that :

- The downdraught problem has been investigated and found to be caused by adverse wind conditions.
- The flue has been properly maintained, cleaned and cleared of blockages.
- The cowl is fitted in accordance with our installation instructions.
- The cowl is fitted to a flue system suitable for the appliance and fuel it serves.
- The cowl is not damaged, painted or modified in any way.





CHIMNEY PROBLEM CHECK LIST

All flues should be checked for blockages caused by falling soot, birds nests or masonry debris, faults that will usually be revealed by sweeping. This should be done regularly, particularly when wood or solid fuel has been burned. Any holes in the chimney structure should be repaired, as air leakages into a flue will cool the flue gases, reducing the up draught, and can also cause the emission of toxic fumes. An efficient fire must have a good air supply. A common cause of air starvation is excessive draught proofing (particularly when UPVC replacement windows have been fitted or cavity insulation), and additional ventilation may therefore have to be fitted adjacent to the fire, a test is for a door or a window left open. Like all mechanical products the method of fixing should remain rigid and may need to be checked occasionally whilst in use, especially in areas subject to high winds and altitude.



Sister Companies with:

CROYDON FIREPLACES



By Appointment to
His Majesty The King
Chimney Sweeps
Milborrow Chimney Sweeps
Crawley Down

MILBORROW

"The Flueologist"

CHIMNEY SWEEPS



EUROCOWL

Flue & Chimney Solutions

Karl Evans

National Sale Rep

07801100018

Parkfields Farm
Hophurst Lane
Crawley Down
West Sussex
RH10 4LN

info@eurocowl.co.uk

www.eurocowl.co.uk

0208 684 1495 / 023 8086 3179

***For the Full Range of Eurocowl Products,
Contact your local Stockist :***

